

Serial No: 10/786,802

Docket No: 2002-0319

CLAIMS

1 1. (Currently Amended) A method for use in a communication network,
2 the method comprising advertising an amount of available bandwidth for a link in
3 response to said available bandwidth having crossed any one of a plurality of fixed
4 bandwidth thresholds ~~that are independent of the amount of bandwidth available for~~
5 ~~the link at a given time,~~

6 wherein said communication network allocates bandwidth to circuits
7 established over said link in discrete bandwidth amounts,

8 and wherein said plurality of bandwidth thresholds are each a function of said
9 discrete bandwidth amounts.

1 2. Canceled.

1 3. (Currently Amended) The method of ~~claim 2~~ claim 1 wherein said
2 plurality of bandwidth thresholds are each a predetermined amount smaller than a
3 respective one of said discrete bandwidth amounts.

1 4. (Currently Amended) The method of ~~claim 2~~ claim 1 wherein
2 individual circuits set up over said link each utilize a respective number of time slots,
3 and wherein each of said discrete bandwidth amounts corresponds to a respective
4 number of said time slots.

1 5. (Original) The method of claim 4 wherein each of said individual
2 circuits is an STS-N circuit having N time slots, where N is a value selected for each
3 circuit from among a predefined set of values.

1 6. (Original) The method of claim 1 wherein said network utilizes a
2 predefined routing protocol, said protocol including routing messages that are
3 communicated among switches within said communication network, and wherein an
4 individual one of said messages is an available bandwidth message that is

Serial No: 10/786,802

Docket No: 2002-0319

5 transmitted, by at least one of said switches to which said link is connected, to at
6 least another one of said switches.

1 7. (Original) The method of claim 6 wherein said predefined routing
2 protocol is PNNI and wherein said available bandwidth message is a link PTSE
3 defined by said PNNI protocol.

1 8. (Currently Amended) A method for use in a communication network
2 comprising a plurality of switches interconnected by a plurality of links, the method
3 comprising
4 setting up circuits through said network, each circuit being set up over a path
5 that includes two or more of said switches and one or more of said links and each
6 circuit having a particular amount of bandwidth selected from a plurality of
7 predetermined circuit bandwidths, and
8 responsive to a request to set up through said network an additional circuit
9 having a desired amount of bandwidth, identifying a path through said network that
10 includes links each having at least that amount of available bandwidth,
11 wherein it is determined how much bandwidth each link has available from
12 available bandwidth messages transmitted within said network, each of the available
13 bandwidth messages indicating an amount of available bandwidth for a respective
14 link, each of at least ones of said available bandwidth messages being transmitted
15 responsive to a determination that the available bandwidth of a particular link has
16 either a) increased from a previous value to a value at least equal to the next higher
17 one of said predetermined circuit bandwidths or b) has decreased from a previous
18 value to a value that is lower than the next lower one of said predetermined circuit
19 bandwidths.

1 9. (Original) The method of claim 8 wherein said circuits each utilize a
2 respective number of time slots, and wherein each of said predetermined circuit
3 bandwidths corresponds to a respective number of said time slots.

Serial No: 10/786,802

Docket No: 2002-0319

1 10. (Original) The method of claim 9 wherein each of said circuits is an
2 STS-N circuit having N time slots, where N is a value selected for each circuit from
3 among a predefined set of values.

1 11. (Original) The method of claim 8 wherein said network utilizes a
2 predefined routing protocol, said protocol including routing messages that are
3 communicated among switches within said communication network, said routing
4 messages including said available bandwidth messages, and wherein said available
5 bandwidth messages are transmitted by at least ones of said switches to others of said
6 switches.

1 12. (Original) The method of claim 11 wherein said predefined routing
2 protocol is PNNI and wherein said available bandwidth message is a link PTSE
3 defined by said PNNI protocol.

1 13. (Original) A method for use in a telecommunications network in
2 which circuits are established over paths within said network, each said path
3 comprising at least two switches interconnected by at least one link, each of said
4 circuits having a provisioned amount of bandwidth selected from a predetermined set
5 of circuit bandwidths, said network being of a type in which available bandwidth
6 messages transmitted within said network indicate an amount of bandwidth currently
7 available on an associated one of said links to provision additional circuits that
8 include that link, the method comprising

9 initiating the transmission of an individual one of said available bandwidth
10 messages in response to a change in the number of said circuit bandwidths that are
11 available on the associated link for the provisioning of new circuits.

1 14. (Original) The invention of claim 13 wherein available bandwidth
2 messages associated with a particular link are transmitted by at least one switch to
3 which that link is connected.

Serial No: 10/786,802

Docket No: 2002-0319

1 15. (Original) The invention of claim 14 wherein said at least one switch
2 transmits said available bandwidth messages associated with a particular link to other
3 switches of said network.

1 16. (Original) The invention of claim 14 wherein said at least one switch
2 transmits said available bandwidth messages associated with a particular link to other
3 switches of said network, but only if it has not done so within a predetermined period
4 of time since it last transmitted an available bandwidth message associated with said
5 particular link.

1 17. (Currently Amended) A telecommunications switch adapted to carry
2 out the method of any one of claims 1, 3 through 7 and 13 through 16.

1 18. (Original) A telecommunications network adapted to carry out the
2 method of any one of claims 8 through 12.